

## PANTA MTV4T-01 (FIM HOMOLOGATED)

PROPERTY	UNIT	FIM Specifications		TEST METHOD	TYPICAL VALUE
		Appendix J - Art 252			
		Min.	Max.		
<b>RON</b>	-	95	102	EN-ISO 5164	<b>102</b>
<b>MON</b>	-	85	90	EN-ISO 5163	<b>89,1</b>
<b>Density at 15° C</b>	kg/m <sup>3</sup>	720	775	EN-ISO 3675	<b>752</b>
<b>Oxygen Content</b>	%wt	-	2,7	Elemental analysis	<b>2,69</b>
<b>Nitrogen Content</b>	%wt	-	0,5	ASTM D 525	<b>&lt;0,1</b>
<b>Oxidation stability</b>	minutes	360	-	ASTM D 3703	<b>&gt;800</b>
<b>Existent gum</b>	mg/100 ml	-	5	EN ISO 6246	<b>&lt;1</b>
<b>Copper corrosion</b>	rating		C1	ISO 2160	<b>1a</b>
<b>Lead Content</b>	g/l	-	0,005	ASTM D 3237	<b>&lt;0,003</b>
<b>Benzene Content</b>	% vol	-	1,0	ASTM D 3606	<b>&lt;0,5</b>
<b>Reid vapour pressure</b>	hPa	-	900	ASTM D 323	<b>488</b>
<b>Sulphur content</b>	ppm		10	EN ISO 20884	<b>&lt;10</b>
<b>Aromatic content</b>	%vol	-	35	ASTM D 1319	<b>&lt;35</b>
<b>Olefin content</b>	%vol	-	18	ASTM D 1319	<b>&lt;18</b>
<b>Total diolefin</b>	% wt	-	1,0	GCMS/HPLC	<b>&lt;1</b>
<b>Distillation:</b>					
<b>Evaporated at 70 °C</b>	%vol	22	47	ISO 3405	<b>28</b>
<b>Evaporated at 100 °C</b>	%vol	46	71		<b>58</b>
<b>Evaporated at 150 °C</b>	%vol	75	-		<b>89</b>
<b>Final Boiling Point</b>	°C	-	210		<b>159</b>
<b>Residue</b>	%vol	-	2		<b>0,9</b>

### PANTA Distribuzione S.p.A

#### Sede Legale e Amministrativa

S.S. 235 - Km. 47+980 - 26010 Bagnolo Cremasco (CR)  
Tel. 0373 235111 - Fax 0373 235156

### PANTA Racing

S.S. 235 - Km. 47+980 - 26010 Bagnolo Cremasco (CR)  
T. 0373 235111 - E-mail: fuelorder@panta.it

### Sedi Operative

Corso Alessandria, 486 - 14100 Asti - T. 0373 235140  
Via Luigi Canina, 7 - 15033 Casale Monferrato (AL)  
T. 0142 466103 - Fax 0142 466369  
E-mail: spedizionipiemonte@panta.it  
S.S. 235 - Km. 47+980 - 26010 Bagnolo Cremasco (CR)  
T. 0373 235163

### Altre Sedi

Via Montefeltro, 4 - 20156 Milano  
T. 02 300598200 / 202  
Strada Cipata, 79 - 46100 Mantova  
T. 0376 378.1  
Via Nizza, 262 - 10126 Torino  
T. 011 2173337